Ka Shing Enterprise (H.K.) Ltd.

ROOM 1706 NEW TERRITORIES TSUEN WAN HO LIK CENTRE, 66A SHA TSUI ROAD
Tel:26280661 Fax: 24902700
Email: project@kashingehk.com
Website: www.kashingehk.com

EVERGOOD

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

CAM LOCK SPECIFICATION SHEET

|		
Item Descriptions	EVERGOOD (P.R.C.) Security Safe Cam Lock (103)	Illustration/ Drawing
Dimension	Φ23.5 x 36.5 mm	
Model	AG-8A	
Finish	Polished Stainless Steel	
Origin	P.R.C.	
Manufacturer	EVERGOOD (P.R.C.)	
Source	Ka Shing Enterprises (H.K) Limted Mr. Ivan Lau / Mr. GilmanYuen	
Contact Tel/Fax E-mail Website	(852) 2628-0661 / (852) 2490-2700 project@kashingehk.com www.kashingehk.com	

Model 103, EVERGOOD security safe cam lock, is an essential component for securing personal belongings and important documents. It is a simple yet highly effective locking mechanism that ensures maximum security. Here is how you can use a security safe cam lock:

Instruction:
1. Select a suitable location for your safe: The first step is to choose the perfect spot to install your security safe. Make sure it is hidden from view and not easily accessible.

2. Install the cam lock: Once you have selected the location, you need to install the cam lock. Read through the instructions carefully and follow them step by step to ensure that you install the cam lock correctly.

3. Insert the key and lock the safe: Once the cam lock is installed, insert the key into the lock and twist it clockwise to lock the safe. Ensure that the lock is fully engaged and the safe door is secure.

4. Keep the key safe: It is vital to keep the key to your safe in a secure location where it is difficult for others to find. Consider storing the key in a fireproof safe or a lockbox.

5. Regularly check the lock: Regularly check the cam lock to ensure that it is functioning correctly. If you notice any problems or issues, seek the help of a professional locksmith.

Normal

型号Model	规格Size
1033	D19L30

Note:

All information of the above is for reference only. No prior notice is made if any changes.

Drawing

15

M19X1

ø23.5

2

L

4.5