





PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	American Standard (Thailand) "Harmony"	Illustration/ Drawing
	Close coupled dual flush high P-trapway washdown watercloset with Horizontal	用水效益標面 Water
	outlet; 3.1/4.7 litres/cycle in WELS Grade	Efficiency Label
	1; Registration No. WC 21-0368	
	1, Registration 1vo. vv 2 21 0300	
Outlet	H.O. trapway 190 mm	
	S-trap, RI 140-160 mm	
		1
Dimensions	L660 x W388 x H790 mm	
Model	TF3253PJ/4313PJ	
		7
Material / Colour	Vitreous China / White	
Manufacturer	American Standard (Thailand)	
Source	Ka Shing Enterprises (H.K) Limted	
	Mr. Ivan Lau / Mr. GilmanYuen	
		*
Contact Tel/Fax	(852) 2628-0661 / (852) 2490-2700	
E-mail	kashing.project@gmail.com	
Website	www.kashingehk.com	
		The state of the s
		140
		390
		190
		-RI- 352
		RI: 140-160 mm
		388
		660 380
		285 348 WATER SUPPLY 180-
		410
		412
		FRONT VIEW

Note:

^{*} All information of the above is for the reference only. No prior notice is made if any changes.



自願參與用水效益標籤計劃 - 水廁 Voluntary Water Efficiency Labelling Scheme - Water Closets



Certificate 註冊證書

legistration

茲證明 This is to certify that

TF3253PJ/4313PJ =3253PJ-XX+4313PJ-XX

將下列水廁在本計劃內註冊:

has registered the following water closet under this scheme:

準 子 / Brand : American Standard + WDI

型 號 / Model : 3253PJ-XX + 4313PJ-XX + B4900H

種 類 / Category : Close-coupled Suite

原產地 / Country or Region Origin : Thailand (WC Pan & Cistern)
XX – denotes colour variants China (Flushing Valve)

XX – denotes colour variants

在用水效益標籤上展示的標誌 Symbolic Presentation on the Water Efficiency Label : 滴水點 Water droplet(s)

用水效益級別 : 1 Water Efficiency Grade

全沖水量 : 4.7 公升/沖廁 litres/flush

低沖水量 : 3.1 公升/沖廁 litres/flush

簽發日期: Date of Issue:

9 September 2021





水務署署長(張業駒代行) for Director of Water Supplies

+ 上述水廁具額外節水功能,即:重用洗盥水作沖廁用途。 for Director of Water Supplies

The above water closet is equipped with additional water saving feature, that is: re-use the water collected from wash basin for flushing purpose



Tel:26280661 Fax: 24902700 Email: project@kashingehk.com Website: www.kashingehk.com

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	WDI (PRC) Adjustable plastic inlet valve	Illustration/ Drawing			
Dimensions	Refer to drawing	00			
Model	B3800E				
Material	Plastic				
Manufacturer	WDI (PRC)				
Supplier	Ka Shing Enterprises (H.K) Limted				
	Mr. Ivan Lau / Mr. GilmanYuen				
Contact Tel/Fax	(852) 2628-0661 / (852) 2490-2700				
E-mail	kashing.project@gmail.com				
Website	www.kashingehk.com	60 98 26.5 88 20.5 88 20.5 88 20.5 88 20.5			

Note: The color of the above fittings may be varied without further notice.

^{*} All information of the above is for the reference only. No prior notice is made if any changes.



水務署 Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 Our ref. 來函檔號

Your ref.

: (4) in WSD 3321/2020 T/J(401/2020)

電話 Tel.

傳真 Fax.

: 2824 0578

23 June 2020



Approval of "WDI" Float Operated Valve (General Acceptance No. C20200498F)

Your letters ref. BE/L20319/20 and BE/L20359/20 dated 15 April 2020 and 22 May 2020 respectively refer.

Having considered the test report ref. RACA059rl issued on 19 May 2020 by Ideal Test Consultants Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

WDI (Xiamen) Technology Inc

Country of Origin:

the Mainland of China

Brand:

WDI

Details of Fitting:

1/2" Plastic float operated valve

Model:

B3800E

Body Markings:

WDI

Expiry Date:

25 March 2025





Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(CHAN Chung-kun)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue ME/MC] - with soft copy only



Website: www.kashingehk.com

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions WDI (PRC) Adjustable 3/6L dual flush Illustration/ Drawing valve with lockable design for cistern lid Dimensions Refer to drawing Model B4900H Material Plastic WDI (PRC) Manufacturer Supplier Ka Shing Enterprises (H.K) Limted Mr. Ivan Lau / Mr. GilmanYuen Contact Tel/Fax (852) 2628-0661 / (852) 2490-2700 E-mail kashing.project@gmail.com Website www.kashingehk.com height of overflow pipe Φ60 **(P**)

Note: The color of the above fittings may be varied without further notice.

^{*} All information of the above is for the reference only. No prior notice is made if any changes.



水務署 Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 Our ref. 來函檔號 Your ref.

(4) in WSD 3321/2020 T/J(399/2020)

電話 Tel.

傳真

2824 0578

15 June 2020



Approval of "WDI" Flush Valve (General Acceptance No. C20200454F)

Your letters ref. BE/L20317/20 and BE/L20354/20 dated 15 April 2020 and 19 May 2020 respectively refer.

Having considered the test report ref. RACA058 issued on 9 April 2020 by Ideal Test Consultants Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

WDI (Xiamen) Technology Inc

Country of Origin:

the Mainland of China

Brand:

WDI

Details of Fitting:

2" Plastic dual flush valve

Model:

B4900H

Body Markings:

WDI B4900

Expiry Date:

2 April 2025





Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(CHAN Chung-kun)

for Director of Water Supplies

Encl.

C.C.

WSD 3321/1/82] - without catalogue ME/MC] - with soft copy only