



Ka Shing Enterprise (H.K.) Ltd.

ROOM 1706 NEW TERRITORIES TSUEN WAN HO LIK CENTRE, 66A SHA TSUI ROAD

Tel:26280661 Fax: 24902700

Email: project@kashingehk.com

Website: www.kashingehk.com

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Model</p> <p>Dimensions</p> <p>Material</p> <p>Manufacturer</p> <p>Source</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>Bobrick (USA) "Classic Series" Recessed paper towel dispenser</p> <p>B-359</p> <p>285 x 395 x 100mm</p> <p>Heavy-gauge Stainless Steel</p> <p>Bobrick Washroom Equipment Inc. (USA)</p> <p>Ka Shing Enterprises (H.K.) Limited Mr. Ivan Lau / Mr. Gilman Yuen (852) 2628-0661 / (852) 2490-2700 project@kashingehk.com www.kashingehk.com</p>	<p style="text-align: center;">Illustration/ Drawing</p> <p>The illustration shows a stainless steel recessed paper towel dispenser. The front view shows a door with a lock and keyhole at the top, a paper towel dispenser mechanism in the middle, and a shelf at the bottom. The technical drawing provides the following dimensions: overall width 12-3/4" (325mm), overall height 17-3/16" (435mm), door width 10-7/8" (275mm), door height 15-5/16" (390mm), door thickness 1" (25mm Typ.), and a 3/13" (5mm) gap at the bottom. Mounting points are marked with 'S' and a 2" (50mm) offset from the wall.</p>
<p>MATERIALS:</p> <p>Cabinet — 18-8, type-304, heavy-gauge stainless steel. All-welded construction. Exposed surfaces have satin finish.</p> <p>Flange — 18-8, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Drawn, one-piece, seamless construction.</p> <p>Door — 18-8, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Double-pan-back construction is warp-resistant. Secured to cabinet with a welded, full-length stainless steel piano-hinge. Equipped with a stainless steel cable door-swing limiter and tumbler lock keyed like other Bobrick washroom accessories.</p> <p>Paper Towel Dispenser — 18-8, type-304, 22-gauge (0.8mm) stainless steel. Dispenses C-fold or multifold paper towels.</p> <p>Capacity: 350 C-fold or 475 multifold paper towels.</p> <p>Shelf — 18-8, type-304, 22-gauge (0.8mm) stainless steel with satin finish.</p> <p>Optional: Order Bobrick Part No. 369-130 TowelMate® Accessory Module has towel guide angle with 90 degree return to prevent paper towels from falling forward when door is opened for servicing. TowelMate Accessory Support Rod allows dispenser to dispense paper towels one at a time without tabbing, tearing, bulging, sagging and bunching.</p> <p>OPERATION:</p> <p>Paper towel dispenser will dispense C-fold or multifold paper towels without adjustment or use of adapters.</p> <p>INSTALLATION:</p> <p>Provide framed rough wall opening 11-1/4" wide x 15-5/8" high (285 x 395mm). Minimum recessed depth required to finish face of wall is 4" (102mm). Allow clearance for construction features that may protrude into rough wall opening from opposite wall. Coordinate with mechanical engineer to avoid pipes, vents, and conduits in wall. Mount unit in wall opening with shims between framing and cabinet at all points indicated by an S, then secure unit with #8 x 1-1/4" (32mm) sheet-metal screws (not furnished by manufacturer).</p> <p>SPECIFICATION:</p> <p>Recessed paper towel dispenser shall be type-304 stainless steel with all-welded construction; exposed surfaces have satin finish. Flange shall be drawn, one-piece, seamless construction. Door shall be secured to cabinet with a welded, full-length, stainless steel piano-hinge and equipped with a stainless steel cable door-swing limiter and tumbler lock keyed like other Bobrick washroom accessories. Shelf shall be stainless steel with satin finish. Paper towel dispenser shall dispense 350 C-fold or 475 multifold paper towels without additional adapters or trays.</p>		

* All information of the above is for the reference only. No prior notice is made if any changes.