



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Model</p> <p>Dimensions</p> <p>Material/color</p> <p>Manufacturer</p> <p>Source</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>Bobrick (USA) Surface-mounted automatic hand dryer, 220-240V</p> <p>B-710E</p> <p>L275 x W130 x H280 mm</p> <p>ABS/ Grey</p> <p>Bobrick Washroom Equipment Inc. (USA)</p> <p>Ka Shing Enterprises (H.K.) Limited Mr. Ivan Lau / Mr. Gilman Yuen</p> <p>(852) 2628-0661 / (852) 2490-2700</p> <p>project@kashingehk.com</p> <p>www.kashingehk.com</p>	<p style="text-align: center;">Illustration/ Drawing</p> <div style="text-align: center;"> </div> <div style="text-align: center;"> </div>								
<p>MATERIALS:</p> <p>Cover — One-piece, 3/32" (2.6mm) thick fire-retardant, molded, high-quality, high-impact, pale grey (Bobrick color #889) ABS plastic, 5-V rated. Cover is secured to mounting base with three flat-head stainless steel screws.</p> <p>Mounting Base and Fan Housing — 5-64" (2.0mm) thick fire-retardant molded grey plastic with high gloss finish. Air-inlet grille fits into bottom of mounting base. Air-outlet grille is secured between fan housing and mounting base.</p> <p>Motor — 115V AC, 90 W, 60 Hz, 2500 rpm. Brushless, external rotor motor. Sealed ball bearings at both ends of drive shaft; maintenance free. Equipped with an automatic thermal-overload switch.</p> <p>Fan — Dynamically balanced 5-15/64" (133mm) diameter centrifugal fan with multiple metallic vanes. Directs airflow from heating element at 90 cfm, mixes air to provide uniform temperature.</p> <p>Heating Element — Coiled nickel-chrome heating element is protected by an automatic thermal-overload switch. Heating element, which is located on inlet side of fan, heats air without hot spots — inaccessible to vandals.</p> <p>Electronic Control — Infrared sensor automatically turns dryer on when hands are held under air-outlet opening and across path of sensor. Remove hands from path of sensor and dryer stops. Electronic sensor has automatic shutoff approximately two minutes after dryer turns on if an inanimate object, such as tape or chewing gum, is placed across sensor lens. After inanimate object is removed, electronic sensor automatically resets itself and dryer operates normally.</p>		<p>*RECOMMENDED MOUNTING HEIGHTS</p> <table border="1"> <tr> <td>Children's Washrooms, ages 3-4</td> <td>36" (915mm)</td> </tr> <tr> <td>Children's Washrooms, ages 5-8</td> <td>40" (1015mm)</td> </tr> <tr> <td>Children's Washrooms, ages 9-12</td> <td>44" (1120mm)</td> </tr> <tr> <td> Universal Design</td> <td>48" (1219mm)</td> </tr> </table> <p><small>*Bottom screw hole of mounting base to finish face of floor</small></p>	Children's Washrooms, ages 3-4	36" (915mm)	Children's Washrooms, ages 5-8	40" (1015mm)	Children's Washrooms, ages 9-12	44" (1120mm)	Universal Design	48" (1219mm)
Children's Washrooms, ages 3-4	36" (915mm)									
Children's Washrooms, ages 5-8	40" (1015mm)									
Children's Washrooms, ages 9-12	44" (1120mm)									
Universal Design	48" (1219mm)									

* All information of the above is for the reference only. No prior notice is made if any changes.