



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Bobrick (USA)"Contura Series" Recessed multi-roll toilet tissue dispenser
Model	B-4388
Dimensions	320 x 190 x 151 mm
Material	Stainless Steel/ Satin
Manufacturer	Bobrick Washroom Equipment Inc. (USA)
Source	Ka Shing Enterprises (H.K.) Limited Mr. Ivan Lau / Mr. Gilman Yuen
Contact Tel/Fax	(852) 2628-0661 / (852) 2490-2700
E-mail	project@kashingehk.com
Website	www.kashingehk.com

Illustration/ Drawing

Rough Wall Opening
 6-1/4" (160mm) wide
 11-1/4" (290mm) high
 3-1/8" (80mm) minimum recessed depth

FRONT VIEW DIMENSIONS:
 Total height: 12-1/2" (320mm)
 Total width: 7-9/16" (190mm)
 Mounting hole spacing: 6-1/16" (155mm)
 Mounting hole diameter: 1-3/8" (25mm) Typ.

INSTALLATION DIMENSIONS:
 Finish Face of Wall to Pivot Point: 2-15/16" (75mm)
 Mounting hole diameter: 1-3/4" (44mm) Typ.
 Recommended Mounting Height Off Floor: 28" to 36" (710 to 915mm)
 Recommended Mounting Height Off Floor For Accessible Design: 28" (710mm)

MATERIALS:
Cabinet — 18-8, type-304, 22-gauge (0.8mm) stainless steel. Welded construction. Exposed surfaces have satin finish.
Flange — 18-8, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Drawn, one-piece, seamless construction. Radius on corners and return edges complement corners and edges of door.
Door — 18-8, type-304, 22-gauge (0.8mm) stainless steel with 18-gauge (1.2mm) stainless steel door frame. Exposed surfaces have satin finish. Front of door is drawn, one-piece, seamless construction and has same degree of arc as other Bobrick ConturaSeries washroom accessories. Radius on corners and edges of door complement other ConturaSeries accessories. Secured to cabinet with two rivets. Equipped with a flush tumbler lock keyed like other Bobrick washroom accessories.
Dispensing Mechanism, Inner Housing, and Cam — 18-8, type-304, 18-gauge (1.2mm) stainless steel.
Spindles (2) — Heavy-duty, one-piece, molded ABS. Theft-resistant, spindles retained in dispensing mechanism when door is locked.

OPERATION:
 Unit holds two standard-core toilet tissue rolls up to 5-1/4" (133mm) diameter (1800 sheets). Tissue rolls are loaded and locked into dispensing mechanism. Extra roll automatically drops in place when bottom roll is depleted. Depleted rolls can only be removed after unlocking door.

INSTALLATION:
 Provide framed rough wall opening 6-1/4" wide x 11-1/4" high (160 x 290mm). Minimum recessed depth required to finish face of wall is 3-1/8" (80mm). Allow clearance for construction features that may protrude into opening from opposite wall. Coordinate with mechanical engineer to avoid pipes, vents, and conduits. Mount unit in wall opening with shims between framing and cabinet at all points indicated by an S, then secure unit with four #10 x 5/8" (4.8 x 16mm) sheet-metal screws (not furnished).

SPECIFICATION:
 Recessed multi-roll toilet tissue dispenser shall be type-304 stainless steel with welded construction, including dispensing mechanism, inner housing and cam; exposed surfaces shall have satin finish. Front of toilet tissue dispenser door shall be drawn, one-piece, seamless construction and shall have same degree of arc and match other Bobrick ConturaSeries accessories in the washroom. Radius on corners and edges of flange and door shall complement other Bobrick ConturaSeries washroom accessories. Door shall be secured to cabinet with two rivets and equipped with a flush tumbler lock keyed like other Bobrick washroom accessories. Flange shall be drawn, one-piece, seamless construction. Unit shall dispense two standard-core toilet tissue rolls up to 5-1/4" (133mm) diameter (1800 sheets). Extra roll shall automatically drop in place when bottom roll is depleted. Unit shall be equipped with two heavy-duty, one piece, molded ABS spindles. Theft-resistant, spindles retained in dispensing mechanism when door is locked.

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.