




# Ka Shing Enterprise (H.K.) Ltd.

ROOM 1706 NEW TERRITORIES TSUEN WAN HO LIK CENTRE, 66A SHA TSUI ROAD  
Tel:26280661 Fax: 24902700  
Email: project@kashingehk.com  
Website: www.kashingehk.com



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

## SANITARY WARE SPECIFICATION SHEET

<p><b>Item Descriptions</b></p> <p><b>Model</b></p> <p><b>Dimensions</b></p> <p><b>Material</b></p> <p><b>Manufacturer</b></p> <p><b>Source</b></p> <p><b>Contact Tel/Fax</b></p> <p><b>E-mail</b></p> <p><b>Website</b></p>	<p>Bobrick (USA) "TrimLineSeries™" Stainless steel Surface-mounted dual roll toilet tissue dispenser with hoods</p> <p>B-6999 (Bright Polished) B-69997 (Satin Finish)</p> <p>W315 x L120 x H155mm</p> <p>Stainless Steel / Satin Finish</p> <p>Bobrick Washroom Equipment Inc. (USA)</p> <p>Ka Shing Enterprises (H.K.) Limited Mr. Ivan Lau / Mr. Gilman Yuen (852) 2628-0661 / (852) 2490-2700 project@kashingehk.com www.kashingehk.com</p>	<p><b>Illustration/ Drawing</b></p> 
<p><b>MATERIALS:</b></p> <p><b>Shell and Flange</b> — 18-8, Type-304, 22-gauge (0.8mm) stainless steel. Drawn, one-piece, seamless construction with four countersunk mounting holes.</p> <p><b>Support Posts (4)</b> — Heavy-duty cast zamak with chrome-plated finish.</p> <p><b>Hoods (2)</b> — 18-8, Type-304, 18-gauge (1.2mm) stainless steel. Hoods hinged to shell.</p> <p><b>Spindles (2)</b> — Chrome-plated plastic equipped with heavy-duty internal springs.</p> <p><b>Designer's Note:</b> Theft-resistant toilet tissue spindles, which are removable only with special key provided, are available as an optional accessory - part no. 283-604. 22" 560mm</p> <p><b>INSTALLATION:</b></p> <p>Mount unit on wall or partition with four sheet-metal screws, furnished by manufacturer, at points indicated by an S. For partitions with particle-board or other solid core, secure with sheet-metal screws furnished, or provide through-bolts, nuts, and washers.</p> <p>For hollow-core metal partitions, provide solid backing into which the furnished sheet-metal screws can be secured.</p> <p>For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws furnished.</p> <p>For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws furnished, or provide 1/8" (3mm) toggle bolts or expansion bolts.</p> <p><b>SPECIFICATION:</b></p> <p>Surface-mounted dual-roll toilet tissue dispenser shall be Type-304 stainless steel with _____ (insert one: bright polished or satin) finish. Shell and flange shall be 22 gauge (6.8mm) and have drawn, one-piece, seamless construction. Unit shall be equipped with 18-gauge (1.2mm) hoods hinged to shell. *Spindles shall be chrome-plated plastic with heavy-duty internal springs.</p> <p>*Theft-resistant spindle (part No. 283-604) available as a replacement part.</p>		

### Note:

\* All information of the above is for the reference only. No prior notice is made if any changes.