



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Bobrick (USA) "TrimLine" Surface mounted ADA hand dryer</p> <p>Model B-7128</p> <p>Dimensions L350 x W100 x H345 mm</p> <p>Material/Finish Stainless Steel/ Satin Finish</p> <p>Manufacturer Bobrick Washroom Equipment Inc. (USA)</p> <p>Source Ka Shing Enterprises (H.K.) Limited Mr. Ivan Lau / Mr. Gilman Yuen</p> <p>Contact Tel/Fax (852) 2628-0661 / (852) 2490-2700</p> <p>E-mail project@kashingehk.com</p> <p>Website www.kashingehk.com</p>		<p>Illustration/ Drawing</p> <p>Weight: 5.4 Kgs</p> <p>Electrical Supply: 208/240 volts, 6.8-7.8 Amp, 1400-1900 Watts; 115 volts, 15 Amp, 1725 Watts</p> <p>Approvals: 208/240V: cULus Listed, VDE, CCC approved, CE marked; 115V: cULus Listed</p> <p>Control System: Automatic, infrared, no-touch</p> <p>Sensor Range: 100mm vertically under outlet</p> <p>Air Volume: 130m³/h</p> <p>Air Velocity: 28 m/s</p> <p>Air Outlet Temperature: 54°C @ 20°C ambient</p> <p>Noise Level: 73 dBA</p> <p>Mounting Base: 20-gauge (1.5mm) plated steel with four 0.236" (6mm) diameter mounting holes.</p> <p>Motor: Universal, 1/7 hp, 8000 rpm, on resilient mounting. Sealed ball bearing at drive-shaft end and self-lubricating sleeve bearing at nondrive end. Equipped with automatic thermal overload switch.</p> <p>Fans: Two balanced, double-inlet centrifugal fans are mounted on motor shaft; directs airflow over heating element at 71 cfm.</p> <p>Heating Element: Two coiled nickel-chrome heating elements are mounted in mica frame and protected by automatic thermal-overload switches. Heating elements, heat air without hot spots — inaccessible to vandals.</p> <p>Electronic Control: Infrared sensor automatically turns dryer on when hands are held under air-outlet opening and across path of sensor. Remove hands from path of sensor and dryer stops. Electronic sensor has automatic shutoff approximately 1-1/2 minutes after dryer turns on if an inanimate object is placed across air-outlet opening. After inanimate object is removed, electronic sensor automatically resets itself and dryer operates normally.</p>
--	--	---

* All information of the above is for the reference only. No prior notice is made if any changes.