



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p>	<p>Delabie (France) "BINOPTIC" Wall-mounted electronic liquid soap dispenser with 230/6V transformer 1-litre</p>	<p style="text-align: center;">Illustration/ Drawing</p>																
<p>Model</p>	<p>512051P</p>																	
<p>Spout length</p>	<p>115mm</p>	<p>Total hygiene: no manual contact</p>																
<p>Material</p>	<p>Chrome plated 304 stainless steel</p>	<p>Comfort: automatic soap dispenser</p>																
<p>Manufacturer</p>	<p>Delabie (France)</p>	<p>No waste pump dispenser</p>																
<p>Source</p>	<p>Ka Shing Enterprises (H.K) Limited Mr. Ivan Lau / Mr. Gilman Yuen</p>	<p>Liquid or foam soap or hydroalcoholic gel</p>																
<p>Contact Tel/Fax</p>	<p>(852) 2628-0661 / (852) 2490-2700</p>																	
<p>E-mail</p>	<p>project@kashingehk.com</p>																	
<p>Website</p>	<p>www.kashingehk.com</p>																	
<p>DESCRIPTION</p> <p>BINOPTIC wall-mounted electronic soap dispenser Ref. 512051P (Chrome-plated 304 stainless steel) Ref. 512051S (Satin finish 304 stainless steel) Ref. 512051BK (Matte black 304 stainless steel) Wall-mounted electronic soap dispenser. Liquid or foam soap or hydroalcoholic gel dispenser. No manual contact: infrared cell detects hands automatically. Chrome-plated 304 stainless steel spout. No waste pump dispenser. Independent electronic housing and removable tank enable installation beneath the washbasin. Automatic soap dispenser: mains supply with 230/6V transformer. For vegetable-based liquid soap with maximum viscosity of 3,000 mPa.s or specific foam soap. Compatible with hydroalcoholic gel Total spout length: 115mm. Supplied with 1-litre tank.</p>																		
<p>TECHNICAL CHARACTERISTICS</p> <p>BINOPTIC wall-mounted electronic soap dispenser - Ref. 512051P</p> <table border="1"> <tr> <td>Supply</td> <td>Mains supply 230/6V</td> </tr> <tr> <td>Technology</td> <td>Infrared detection</td> </tr> <tr> <td>Height</td> <td>333mm (tank and electronic unit)</td> </tr> <tr> <td>Length</td> <td>115mm</td> </tr> <tr> <td>Spout length</td> <td>98mm</td> </tr> <tr> <td>Volume</td> <td>1-litre tank</td> </tr> <tr> <td>Finish</td> <td>Chrome-plated 304 stainless steel</td> </tr> <tr> <td>Norms</td> <td>CE</td> </tr> </table>		Supply	Mains supply 230/6V	Technology	Infrared detection	Height	333mm (tank and electronic unit)	Length	115mm	Spout length	98mm	Volume	1-litre tank	Finish	Chrome-plated 304 stainless steel	Norms	CE	
Supply	Mains supply 230/6V																	
Technology	Infrared detection																	
Height	333mm (tank and electronic unit)																	
Length	115mm																	
Spout length	98mm																	
Volume	1-litre tank																	
Finish	Chrome-plated 304 stainless steel																	
Norms	CE																	

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.





