



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Dimensions</p> <p>Model</p> <p>Material/ Finish</p> <p>Manufacturer</p> <p>Source</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>Delabie (France) "Binoptic" Wall concealed chrome plate spout for partition wall or panel, 230V AC supply ; nominated flow rate 3.4 L/min in WELS Grade 2; Registration No. TN 19-0052</p> <p>Refer to drawing</p> <p>379DER</p> <p>Brass/ Chrome Plated</p> <p>Delabie (France)</p> <p>Ka Shing Enterprises (H.K) Limited Mr. Ivan Lau / Mr. GilmanYuen</p> <p>(852) 2628-0661 / (852) 2490-2700 project@kashingehk.com www.kashingehk.com</p>	<p style="text-align: center;">Illustration/ Drawing</p> <p>ADVANTAGES</p> <ul style="list-style-type: none"> Exceptional water savings: 90% Hygiene: no manual contact Independent IP65 electronic control unit LED diagnostic aid 												
<p>Electronic basin tap for cross wall installation. Independent IP65 electronic control unit. 230/12V mains supply with transformer. Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant flow straightener. Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Sensor at the end of the spout optimises presence detection. Filters and solenoid valves M3/8". Chrome-plated brass body. Chrome-plated spout L. 205mm for cross wall installation_ 190mm. Cable for sensor L. 120mm, flexibles and mounting all pass through the same hole. Anti-blocking security. Spout with smooth interior and low volume of water (reduces niches where bacteria can develop). Suitable for people with reduced mobility.</p> <table border="1" style="width: 100%;"> <tr> <td>Supply</td> <td>230/12V mains supply</td> </tr> <tr> <td>Connector</td> <td>M3/8"</td> </tr> <tr> <td>Technology</td> <td>Electronic</td> </tr> <tr> <td>Spout length</td> <td>205mm</td> </tr> <tr> <td>Flow rate</td> <td>3 lpm</td> </tr> <tr> <td>Norms</td> <td>ACS CE V W G WWRAS</td> </tr> </table>		Supply	230/12V mains supply	Connector	M3/8"	Technology	Electronic	Spout length	205mm	Flow rate	3 lpm	Norms	ACS CE V W G WWRAS	
Supply	230/12V mains supply													
Connector	M3/8"													
Technology	Electronic													
Spout length	205mm													
Flow rate	3 lpm													
Norms	ACS CE V W G WWRAS													

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

A1

A2

B

C

Note:

* All information of the above is for the reference only. No prior notice is made if any changes.



自願參與用水效益標籤計劃 - 水龍頭
Voluntary Water Efficiency Labelling Scheme - Water Taps

Certificate of Registration 註冊證書



茲證明
This is to certify that

將下列水龍頭在本計劃內註冊：
has registered the following water tap under this scheme :

牌子 / Brand	:	Delabie
型號 / Model	:	379DER
種類 / Type	:	Non-mixing
原產地 / Country or Region Origin	:	France

在用水效益標籤上展示的標誌

Symbolic Presentation on the Water Efficiency Label

: 

滴水點

Water droplet(s)

用水效益級別

Water Efficiency Grade

: 2

with additional merit*

耗水量

Water Consumption

: 3.4

公升/分鐘

litres/minute

*with additional merit of "Automatic closing mechanism"

簽發日期:

Date of Issue:

12 April 2019



水務署

Water Supplies Department



水務署署長(張業駒代行)
for Director of Water Supplies