

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	MEITU (PRC) Plastic circular pneumatic dual flush 3/4.6	Illustration/ Drawing
Model Material Manufacturer Source	P61 Plastic MEITU (PRC) Ka Shing Enterprises (H.K) Limted	
Contact Tel/Fax E-mail Website	Mr. Ivan Lau / Mr. GilmanYuen (852) 2628-0661 / (852) 2490-2700 project@kashingehk.com www.kashingehk.com	
		130

*	411	information	of the	ahova is	for the	roforonco	onh	No prior	notice is	made if any	change
•	All	iniormaiion	i oi ine i	anove is	ior ine	reierence	oniv.	NO prior	nouce is	maae ii anv	cnange

Note:



水 務 署 Water Supplies Department

總部 Headquarters 香港灣仔告士打道七號人境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 Our ref. 來函檔號 Your ref.

(4) in WSD 3321/2021 T/J(471/2021)

電話

Tel.

傳真 Fax.

: 2824 0578

19 April 2021

Dear Sir.

Approval of "OTTER" Flush Valve (General Acceptance No. C20210400F)

Your letters both ref. WRC/21002 dated 16 March 2021 and 29 March 2021 refer.

Having considered the test report ref. J25843 issued on 16 March 2021 by Nutek Systems (HK) Limited, this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

Zhongshan Meitu Plastic Ind Co Ltd

Country of Origin:

the Mainland of China

Brand:

Otter

Details of Fitting:

2" Plastic dual flush valve

Model:

P61

Body Markings:

MEITU

Expiry Date:

6 January 2026





Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(Roger WONG)

for Director of Water Supplies

Encl.

c.c.

WSD 3321/1/82] - without catalogue ME/MC] - with soft copy only