

Note:

Ka Shing Enterprise (H.K.) Ltd.

ROOM 1706 NEW TERRITORIES TSUEN WAN HO LIK CENTRE, 66A SHA TSUI ROAD Tel:26280661 Fax: 24902700 Email: project@kashingehk.com Website: www.kashingehk.com



PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	KITA (PRC) F1/2" x F1/2" x 460mm Toilet saltwater braided hose, 510 mm length with WRAS Approval number: 1909395	Illustration/ Drawing	
Model	BL-99A	SUTE CONTROL OF THE PARTY OF TH	
Finish	Stainless Steel	The state of the s	
Source	Ka Shing Enterprises (H.K) Limted		
	Mr. Ivan Lau / Mr. GilmanYuen		
Contact Tel/Fax	(852) 2628-0661 / (852) 2490-2700		
E-mail	project@kashingehk.com		
Website	www.kashingehk.com		

^{*} All information of the above is for the reference only. No prior notice is made if any changes.



水 務 署 Water Supplies Department

總部 Headquarters 香港灣仔告士打道七號人境事務大樓 48 樓 48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 Our ref.

: (4) in WSD 3321/2021 T/J(48/2021)

電話

Tel.

來函檔號 Your ref. 傳真 Fax. 2824 0578

8 March 2021

Approval of "KITA" Flexible Hose (General Acceptance No. B20210009)

Your letters dated 11 December 2020 and 25 January 2021 refer.

It is noted that the fitting described below has been accepted by the United Kingdom Water Regulations Advisory Scheme (WRAS) to have complied with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations / Scottish Water Byelaws when correctly installed. This Authority accepts that the fitting described below based on the WRAS certificate complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

Ka Shing Enterprises (HK) Ltd

Country of Origin:

the Mainland of China

Brand:

Kita

Details of Fitting:

Range of stainless steel braided PEX lined flexible hose assemblies with brass end connections and EPDM o ring and washers with various end connections options. Maximum working pressure 10.0 bar. Maximum operating temperature 85°C.





Model:

PEX-KITA

Size:

Bore diameters: DN6 & DN8

End connections:

M10, M12, M15, F3/8", F1/2", F3/4", F15, 3/8" BSP (M),

1/2" BSP (M), 3/4" BSP (M)

Body Markings:

PEX-KITA, WRAS & Year of Manufacture YYYY on

crimped connection

WRAS Approval Number: 1909395

Installation Requirements: R001, R008

Expiry Date:

30 September 2024

In view of the acceptance by WRAS, this Authority has no objection to the use of the said fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following installation requirements –

"Installation shall comply with the 'Installation Requirements & Notes' of the WRAS's approval letter concerned." AND

"The inlet flexible hose is applied for the water tap or mixer connection only and installed in the fresh water plumbing systems."

A condition of this acceptance is that the fitting to be installed should be replicas of the sample certified by WRAS and no modification should be made to the fitting. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority. Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(Roger WONG)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue ME/MC] - with soft copy only