

Ka Shing Enterprise (H.K.) Ltd.

ROOM 1706 NEW TERRITORIES TSUEN WAN HO LIK CENTRE, 66A SHA TSUI ROAD Tel:26280661 Fax: 24902700 Email: project@kashingehk.com Website: www.kashingehk.com



PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Mediclinics (Spain) Toilet paper dispenser, Item Descriptions industrial roll, steel, stainless steel AISI 304, satin finish Paper roll capacity Max. Ø 230 L250 x W129 x H250 mm **Dimensions** Model PR2783CS Material/Finish Stainless Steel/ Satin Finish Manufacturer Mediclinics, S.A. (Spain) Source Ka Shing Enterprises (H.K) Limted Mr. Ivan Lau / Mr. GilmanYuen Contact Tel/Fax (852) 2628-0661 / (852) 2490-2700 E-mail project@kashingehk.com Website www.kashingehk.com

Materials & components

- PR2783: steel, 0.8 mm thick, white epoxy finish.
- PR2783C: stainless steel AISI 304, 0.8 mm thick, bright finish.
- PR2783CS: stainless steel AISI 304, 0.8 mm thick, satin finish.
- PR2783B: steel, 0.8 mm thick, black epoxy finish.
- One-piece body, 0,8 mm thick, round Ø 250 mm, fully sealed and with a catch system to prevent the opening of the door. The supports of the screws in the back of the appliance, are acting as an anti-moisture support, as well as slots to avoid the screws damaging the toilet paper. It is mounted on the wall by means of 3 wood screws with their corresponding 5 mm wall plugs. It includes a lock system with standard mediclinics® key, that allows opening the replenishment.
- PA6 plastic shaft, for standard Ø45mm paper rolls tube, with inertial anti-spin retainer. This shaft is removable with 2 different positions to allow variety of paper rolls. It also allows the use of a standard paper roll in case of need.
- One-piece seamless lid, 0.8 mm thick, fully sealed. Fixed to the body by means of rivets that allow swinging down the lid for the replenishment.
- Slot at the front with a plastic viewer that indicates the content
- Back-plate, 0.6 mm thick, with multiple slots for easy installation. Total compatible with PR0783... series.













