



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

## SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Mediclinics "Saniflow® " (Spain) Steel wall mounted push-button hand dryer with rotating nozzle in bright chrome finish	<p>Illustration/ Drawing</p>
Dimensions	L278 x W212 x H248 mm	
Model	E88C	
Material/ Finish	Steel / Bright Chrome Finish	
Manufacturer	Mediclinics, S.A. (Spain)	
Source	Ka Shing Enterprises (H.K) Limited Mr. Ivan Lau / Mr. GilmanYuen	
Contact Tel/Fax	(852) 2628-0661 / (852) 2490-2700	
E-mail	project@kashingehk.com	
Website	www.kashingehk.com	

**General description**

\*Saniflow® push-button hand dryer is the rotating nozzle dryer that is most widely used in the world, regardless of the location to be fitted.

\*These machines also feature easy maintenance, low noise levels and a high level of user safety. Together with an accurate design of components, SANIFLOW dryers boast the most powerful airflow in the world, which, combined with a comfortable drying temperature, reduces drying times to a minimum.

\*With a 1,5 mm. thick steel cover, these hand dryers are available in 5 different finishes (white or black enameled coating, bright, satin and gold plated). These hand dryers are ideal for Heavy traffic Bathrooms.

\*Thus, these are proven models with a long durability and complete reliability, with anti-vandalism features and designed to be installed in high traffic of people such as airports, large hotels, sport centers, large recreational areas and large official organizations, among

**Components & materials:**

**E88:** 1,5 mm. thick steel cover, white enameled coating finish.

**E88B:** 1,5 mm. thick steel cover, matte black finished.

**E88C:** 1,5 mm. thick steel cover, bright finish.

**E88CS:** 1,5 mm. thick steel cover, satin finish.

**E88O:** 1,5 mm. thick steel cover, gold plated finish.

One-piece steel cover fixed to the base by means of 2 vandal-proof lock screws and lock with special Saniflow® wrench.



**Technical Specifications:**

<b>Voltage</b>	220- 240 V
<b>Frequency</b>	50/60 Hz
<b>Electrical Isolation</b>	Class I
<b>Total power</b>	2,250 W
<b>Consumption</b>	10 A
<b>Motor power</b>	250 W
<b>Rpm</b>	5,500
<b>Heating element power</b>	2,000 W
<b>Dimensions</b>	248x278x212 mm
<b>Weight</b>	5.9 Kg
<b>Cover thickness</b>	1.5 mm
<b>Drying time</b>	29 sec.
<b>Air velocity</b>	100 Km/h
<b>Air temperature (10 cm distance/21°C)</b>	50 °C
<b>Sound pressure (*) (at 2m)</b>	68 dBA
<b>Protection rating</b>	IP23

(\*) According to UNE EN ISO 11201:2010 V2 standard.


Note:



\* All information of the above is for reference only. No prior notice is made if any changes.


**PUSH-BUTTON****Saniflow E88****E88****E88C****E88CS****E88O****Operation**

Press the push-button to initiate the drying process, place the hands under the rotating nozzle into the air outlet and rub them together. The dryer will go on with no interruption for 35 seconds.

**Mounting****Recommended heights distance from the floor**

**H = Distance from floor**

120 cm	115 cm	95 cm	100 cm
47"	45"	37"	40"

**Certificates and Qualifications**