

Tel:26280661 Fax: 24902700 Email: project@kashingehk.com Website: www.kashingehk.com

TOTO

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions TO TO (Japan) Close coupled dual flush Illustration/ Drawing integrated S-trap way washdown watercloset with Horizontal outlet; 3.0/4.5 litres/cycle in WELS Grade1; Registration No. WC 22-0021 Dimensions W365 x D720 x H766 mm Model CW781B/SW781SB Materials / Colour Vitreous China / White TO TO (Japan) Manufacturer Source Ka Shing Enterprises (H.K) Limted Mr. Ivan Lau / Mr. Gilman Yuen Awards Technologies Contact Tel/Fax (852) 2628-0661 / (852) 2490-2700 E-mail project@kashingehk.com Website www.kashingehk.com 墙面进水预留(Rc1/2) 700 (465)——— 出水口中心线 角阀位置W(200) (215) W 安装普通便盖时需另购角阀三件D104N ()建议安装尺寸

Note:

^{*} All information of the above is for the reference only. No prior notice is made if any changes.

註冊號碼 (Registration No.):

WC 22-0021



自願參與用水效益標籤計劃 -水廁 Voluntary Water Efficiency Labelling Scheme - Water Closets

ertificate egistration

> 茲證明 This is to certify that

將下列水廁在本計劃內註冊:

has registered the following water closet under this scheme :

子 / Brand TOTO

號 / Model 型 CW781B + SW781SB + B4900-G

類 / Category Close-coupled Suite

China 原產地 / Country or Region Origin :

(WC Pan, Cistern & Flushing Valve)

在用水效益標籤上展示的標誌

Symbolic Presentation on the Water Efficiency Label

滴水點 Water droplet (s)

用水效益級別

Water Efficiency Grade

全沖水量

Water Hush Volumn (Full)

4.5

1

公升/沖廁 litres/flush

低沖水量

Water Hush Volumn (Reduced)

3.0

公升/沖廁 litres/flush

簽發日期: Date of Issue:

19 January 2022





水務署署長(尤孝賢代行) for Director of Water Supplies

上述水廁具額外節水功能,即:重用洗鹽水作沖廁用途。

The above water closet is equipped with additional water saving feature, that is: re-use the water collected from wash basin for flu



水務署 Water Supplies Department

總部 Headquarters 香港灣仔告士打道七號入境事務大樓 48 樓 48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 Our ref. 來函檔號

Your ref.

(2) in WSD 3321/2021 T/J(580/2021)

電話

Tel.

傳真 Fax.

2824 0578

14 May 2021



Approval of "TOTO" Flush Valve (General Acceptance No. C20210514F)

Your letter ref. L-TT-8460 dated 16 April 2021 refers.

Having considered the test report ref. 204582ST200528 issued on 1 April 2021 by Fugro Technical Services Limited, this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

Voreto (Xiamen) Plumbing Technology Co Ltd

Country of Origin:

the Mainland of China

Brand:

TOTO

Details of Fitting:

2" Plastic dual flush valve

Model:

B4900H-G

Body Markings:

Nil

Expiry Date:

15 March 2026





Proviso: As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(Roger WONG)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue ME/MC] - with soft copy only



Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

Our ref. 來函檔號 Your ref.

(2) in WSD 3321/2021 T/J(842/2021)

電話 Tel.

傳真 Fax.

: 2824 0578

5 July 2021



HF9B208A

Approval of "TOTO" Float Operated Valve (General Acceptance No. C20210695F)

Your letter ref. L-TT-8488 dated 26 May 2021 refers.

Having considered the test report ref. 204582ST200528(1) issued on 20 May 2021 by Fugro Technical Services Limited, this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

TOTO Vietnam Co Ltd

Country of Origin:

Vietnam

Brand:

TOTO

Details of Fitting:

1/2" Plastic float operated valve

Model:

HF9B208A

Body Markings:

TOTO

Expiry Date:

15 March 2026





Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

> "The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

> "The fitting should be used within the range of working pressures specified by the manufacturer." AND

> "The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(Roger WONG) for Director of Water Supplies

Encl.

c.c.

WSD 3321/1/82] - without catalogue

ME/MC

] - with soft copy only