



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

DOOR CLOSER SPECIFICATION SHEET

<p>Item Descriptions</p> <p>SODUN (P.R.C.) 8404BC Door Closer</p> <p>Dimensions 207 x 55 x 40 mm</p> <p>Model 8404BC</p> <p>Finish Silver</p> <p>Origin P.R.C.</p> <p>Manufacturer SODUN (P.R.C.)</p> <p>Source Ka Shing Enterprises (H.K.) Limited Mr. Ivan Lau / Mr. Gilman Yuen</p> <p>Contact Tel/Fax (852) 2628-0661 / (852) 2490-2700</p> <p>E-mail project@kashingehk.com</p> <p>Website www.kashingehk.com</p>	<p>Illustration/ Drawing</p> <div style="display: flex; justify-content: space-around;"> <div data-bbox="1002 651 1203 757"> </div> <div data-bbox="1337 645 1414 768"> <p>银灰 Silver</p> </div> </div> <div style="text-align: center;"> </div>	<p>明装式 / Surface Mounted Type</p> <hr/> <p>A Standard Arm Installation / 标准安装</p> <div style="display: flex; justify-content: space-around;"> </div> <p>B Top Jamb Arm Installation / 门框安装</p> <div style="display: flex; justify-content: space-around;"> </div> <p>C Parallel Arm Installation / 平行安装</p> <div style="display: flex; justify-content: space-around;"> </div>
<p>Functional Characteristics:</p> <ul style="list-style-type: none"> - Suitable for all kinds of commercial doors - ADC12 environmental aluminum alloy casting body - Product performance standard: QB/T2698-2013 - Two speed control valve, adjusting closing speed and latching speed - Delay action (DA) optional - Back-Check (BC) function optional - Fixed power size EN4, can be adjusted to power size EN3 - Built-in anti-external force device protects doors and door frames as well as door closers - Produced according to standard EN1154 - USA and Canada UL Approved - Max. Door Weight 85 KG <p>Compliance with:</p> <ul style="list-style-type: none"> - BS EN 1154:1997 (Power Size 4) <div style="display: flex; justify-content: center; align-items: center; gap: 20px;"> </div>		

Note:

* All information of the above is for reference only. No prior notice is made if any changes.

Specifications								
Model	Dimension (mm)			Hole Spacing (mm)		Applicable door weight (KG)	Applicable door width (mm)	The function
	A	B	C	D	E			
8404BC	207	55	40	50	39	60-85	930-1100	Two speed control valve / Back-Check (BC)

Drawing:

