



PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

DOOR CLOSER SPECIFICATION SHEET

<p>Item Descriptions</p> <p>Dimensions</p> <p>Model</p> <p>Finish</p> <p>Origin</p> <p>Manufacturer</p> <p>Source</p> <p>Contact Tel/Fax</p> <p>E-mail</p> <p>Website</p>	<p>SODUN (P.R.C.) 8403BC Door Closer</p> <p>220 x 54 x 45 mm</p> <p>8403BC</p> <p>Silver</p> <p>P.R.C.</p> <p>SODUN (P.R.C.)</p> <p>Ka Shing Enterprises (H.K.) Limited Mr. Ivan Lau / Mr. Gilman Yuen</p> <p>(852) 2628-0661 / (852) 2490-2700 project@kashingehk.com www.kashingehk.com</p>	<p>Illustration/ Drawing</p> <div style="text-align: right;">  银灰 Silver </div>  <p>明装式 / Surface Mounted Type</p> <p>A Standard Arm Installation / 标准安装</p>  <p>B Top Jamb Arm Installation / 门框安装</p>  <p>C Parallel Arm Installation / 平行安装</p> 
<p>Functional Characteristics:</p> <ul style="list-style-type: none"> - Suitable for all kinds of commercial doors - ADC12 environmental aluminum alloy casting body - Product performance standard: QB/T2698-2013 - Two speed control valve, adjusting closing speed and latching speed - Back-Check (BC) function optional - Fixed power size EN3/EN4 - Built-in anti-external force device protects doors and door frames as well as door closers - Produced according to standard EN1154 - Max. Door Weight 65 KG <p>Compliance with:</p> <ul style="list-style-type: none"> - BS EN 1154:1997 (Power Size 3) 		

Note:

* All information of the above is for reference only. No prior notice is made if any changes.

Specifications								
Model	Dimension (mm)			Hole Spacing (mm)		Applicable door weight (KG)	Applicable door width (mm)	The function
	A	B	C	D	E			
8403BC	220	54	45	202	19	40-65	830-950	Two speed control valve / Back-Check (BC)

Drawing:

