

Ka Shing Enterprise (H.K.) Ltd.

ROOM 1706 NEW TERRITORIES TSUEN WAN HO LIK CENTRE, 66A SHA TSUI ROAD Tel:26280661 Fax: 24902700 Email: project@kashingehk.com Website: www.kashingehk.com



PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SHOWER SEAT SPECIFICATION SHEET

Item Descriptions		ı (P.R.C. coom Sto	.) MT80181 Foldab ol	Illustration/ Drawing		
Dimension	455 x	x 300 x 2	70 mm			
Model	MT8	0181				
Finish	Creat	ny-Whit	e			
Origin	P.R.C	2.				
Manufacturer	Meitt	ı (P.R.C.	.)			
Source		•	erprises (H.K) Lim / Mr. GilmanYuen	ted		
Contact Tel/Fax	(852)	2628-06	561 / (852) 2490-27			
E-mail	proje	ct@kash	ingehk.com			
Website	www	.kashing	ehk.com			
Feature: EXTRA STABILITY FOR UNSTEADY USERS: Permanently fitted in place using the strong frames included, this fold down seat provides unrivalled support and security when compared to shower stools; professionally installed. LIKE A SHOWER STOOL BUT BETTER: This foldable shower seat can remain in the down position or be folded neatly away when not in use, and unlike regular shower stools, it saves you lots of space in your bathroom STYLISH AND CONVENIENT: Most portable bath chairs are not only an eyesore, , they're difficult to transfer in and out of the tub, especially for anyone who has limited mobility or struggles with physical exertion. The simple, minimalist classic white design suits any modern bathroom décor and won't overwhelm the aesthetics BUILT FOR COMFORT AND QUICK CLEANING: Meticulously designed with rounded corners, smooth surfaces and soft edges for comfortable seating and protection again injuries if accidentally bumped. The smooth surfaces also help make cleaning quick and easy MAKES SHOWERING SAFE AND EASY:					list 000000000000000000000000000000000000	
This shower accessory is perfect bending over, shaving or washi	t for any adults	s or elderly w	ho experience discomfort fro	om standing,		
Sample	Test load (kgf)	Duration (minute)	Visual rotate & damage	Remark		
Foldable bathroom stool	150	30	No rotate & damage	Pass	The sample was installed onto a concrete wall (with drilled holes dia. 12mm) made of concrete mix grade 30D10 (cement to BS12: 1978 and Aggregate to BS882: 1973).	

Note:

* All information of the above is for reference only. No prior notice is made if any changes.